

Single Row Terminal Blocks

Kulka® 411 Series

300 Volts



Specifications:

Base, Phenolic, 150° C
 JJ (GDI-30F) Material Available
 Screws, # 2-56 Binder Head, Phil-Slot
 Terminals, Plated Brass
 1-23 Poles
 Wire Range with Wire Binding Screw #18 - #20 Awg - 5 Amps
 The Suitability of These Devices for Greater Currents Shall Be
 Determined in the End-Use Application.
 UL Recognized File No. E47811
 CSA Certified File No. LR19766
 CE

Catalog #	Dimensions		Catalog #	Dimensions	
	A	B		A	B
411 GP 01	0.50	0.75	411 GP 13	3.50	3.75
411 GP 02	0.75	1.00	411 GP 14	3.75	4.00
411 GP 03	1.00	1.25	411 GP 15	4.00	4.25
411 GP 04	1.25	1.50	411 GP 16	4.25	4.50
411 GP 05	1.50	1.75	411 GP 17	4.50	4.75
411 GP 06	1.75	2.00	411 GP 18	4.75	5.00
411 GP 07	2.00	2.25	411 GP 19	5.00	5.25
411 GP 08	2.25	2.50	411 GP 20	5.25	5.50
411 GP 09	2.50	2.75	411 GP 21	5.50	5.75
411 GP 10	2.75	3.00	411 GP 22	5.75	6.00
411 GP 11	3.00	3.25	411 GP 23	6.00	6.25
411 GP 12	3.25	3.50			

* Based on Class B requirements.

Hardware Options:

KT10 = Full Quick Connect (0 Flat)
 KT 11 = Full Quick Connect (45 Bend)
 KT 12 = Full Quick Connect (90 Bend)
 ST = Full Solder
 J410 = Line to Line Jumper
 3/4 ST = Half Solder
 KT 16 = Half Quick Connect (0 Flat)
 KT 17 = Half Quick Connect (45 Bend)
 KT 18 = Half Quick Connect (90 Bend)
 Z = Lug Over the Side (.312)
 1921 = Printed Circuit Pin (.125)
 (Over the Side)

