

# Single Row Terminal Blocks

## Kulka® 699 Series

150 Volts



### Specifications:

- Base, Phenolic, 150° C
- (JJ) GDI-30F Material is Available
- Screws, #6-32 Binder Head, Phil Slot
- Terminals, Plated Brass
- 1-23 Poles
- Wire Range with Wire Binding Screw #14 - #16 Awg - 20 Amps
- The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
- UL Recognized File No. E47811
- CSA Certified File No. LR19766
- CE

Catalog #	Dimensions		Catalog #	Dimensions	
	A	B		A	B
699 GP 01	0.88	1.19	699 GP 13	6.13	6.44
699 GP 02	1.31	1.63	699 GP 14	6.56	6.88
699 GP 03	1.75	2.06	699 GP 15	7.00	7.31
699 GP 04	2.19	2.50	699 GP 16	7.44	7.75
699 GP 05	2.63	2.94	699 GP 17	7.88	8.19
699 GP 06	3.06	3.38	699 GP 18	8.31	8.63
699 GP 07	3.50	3.81	699 GP 19	8.75	9.06
699 GP 08	3.94	4.25	699 GP 20	9.19	9.50
699 GP 09	4.38	4.69	699 GP 21	9.63	10.38
699 GP 10	4.81	5.13	699 GP 22	10.06	10.38
699 GP 11	5.25	5.56	699 GP 23	10.50	10.81
699 GP 12	5.69	6.00			

### Hardware Options:

- KT 46 = Full Quick Connect (0 Flat)
- KT 47 = Full Quick Connect (45 Bend)
- KT 48 = Full Quick Connect (90 Bend)
- J 601 = Line to Line Jumper
- 3/4 ST = Half Solder
- KT 52 = Half Quick Connect (0 Flat)
- KT 53 = Half Quick Connect (45 Bend)
- KT 54 = Half Quick Connect (90 Bend)
- Z = Lug Over the Side (.437)

