

Single Row Terminal Blocks

Kulka® 812 Series

600 Volts

Specifications:

Base, Phenolic, 150° C
 (JJ) GDI-30F Material is Available
 Screws, #8-32 Binder Head, Phil Slot
 Terminals, Plated Brass
 1-18 Poles
 Wire Range with Wire Binding Screw #12 - #14 Awg - 30 Amps
 The Suitability of These Devices for Greater Currents Shall Be
 Determined in the End-Use Application.
 UL Recognized File No. E47811
 CSA Certified File No. LR19766
 CE



Catalog #	Dimensions		Catalog #	Dimensions	
	A	B		A	B
812 GP 01	1.13	1.53	812 GP 10	6.19	6.59
812 GP 02	1.69	2.09	812 GP 11	6.75	7.16
812 GP 03	2.25	2.66	812 GP 12	7.31	7.72
812 GP 04	2.81	3.22	812 GP 13	7.88	8.28
812 GP 05	2.63	2.94	812 GP 14	8.44	8.84
812 GP 06	3.94	4.34	812 GP 15	9.00	9.41
812 GP 07	4.50	4.91	812 GP 16	9.56	9.97
812 GP 08	5.06	5.47	812 GP 17	10.13	10.53
812 GP 09	5.63	6.03	812 GP 18	10.69	11.09

Hardware Options:

- KT 73 = Full Quick Connect (0 Flat)
- KT 74 = Full Quick Connect (45 Bend)
- KT 75 = Full Quick Connect (90 Bend)
- J 602 = Line to Line Jumper
- 3/4 ST = Half Solder
- KT 79 = Half Quick Connect (0 Flat)
- KT 80 = Half Quick Connect (45 Bend)
- KT 81 = Half Quick Connect (90 Bend)
- Z = Lug Over the Side (.641)

