


Renewal Coils - A.C. ①②

A.C. Control Voltages			A.C. Coil ↓ Codes ↓ ②	For use with contactor...			
50 Hz	60 Hz	50/60 Hz		CA7-9...16 Cat. No.	CA7-23...37 Cat. No.	CA7-43 Cat. No.	CA7-60...85 Cat. No.
	12V		12B	TA006	TC006	TD006	TE006
12V			12A	TA404	TC404	TD404	TE404
	24V		24B	TA013	TC013	TD013	TE013
24V			24A	TA407	TC407	TD407	TE407
		24V	24Z	TA855	TC855	TD855	TE855
32V	36V		36	TA481	TC481	TD481	TE481
36V			36A	TA410	TC410	TD410	TE410
42V	48V		48	TA482	TC482	TD482	TE482
48V			48A	TA414	TC414	TD414	TE414
		48V	48Z	TA860	TC860	TD860	TE860
100V	100...110V		110	TA861	TC861	TD861	TE861
110V	120V		120	TA473	TC473	TD473	TE473
		110V	110Z	TA856	TC856	TD856	TE856
120V			120A	TA425	TC425	TD425	TE425
127V			127	TA428	TC428	TD428	TE428
200V	200...220V	200V	220	TA862	TC862	TD862	TE862
	208V		208	TA049	TC049	TD049	TE049
	208V...240V		220W	TA296	TC296	TD296	TE296
220V	240V		240	TA474	TC474	TD474	TE474
220V...230V			230A	TA441	TC441	TD441	TE441
		230V	230Z	TA851	TC851	TD851	TE851
230V...240V			240A	TA440	TC440	TD440	TE440
240V	277V		277	TA480	TC480	TD480	TE480
		240V	240Z	TA858	TC858	TD858	TE858
	347V		347	TA065	TC065	TD065	TE065
	380V		380B	TA067	TC067	TD067	TE067
380V...400V	440V		380	TA071	TC071	TD071	TE071
		400V	400Z	TA863	TC863	TD863	TE863
400V...415V			415	TA457	TC457	TD457	TE457
440V	480V		480	TA475	TC475	TD475	TE475
		440V	440Z	TA859	TC859	TD859	TE859
500V			500	TA479	TC479	TD479	TE479
550V	600V		600	TA476	TC476	TD476	TE476
Price				36	52	62	72



CA7 A.C. coil (typical) - side view



top view

① Other coil voltages available. Contact your Sprecher + Schuh representative for information.


② A.C. Codes in large, bold letters indicate coils that are standard stocked items.

Renewal Coils - D.C. ①②⑤


D.C. Control Voltages	D.C. Coil Codes ↓	For use with contactor...			
		CA7-9C...16C Cat. No.	CA7-23C...37C Cat. No.	CA7-43C Cat. No.	CA7-60D...85D Cat. No.
VDC	Ⓜ				
9V Ⓜ	9D	TA766	TC766	TD766	~
9V Diode Ⓜ	9DD	~	~	~	TE766M
12V	12D	TA708	TC708	TD708	~
12V Diode	12DD	~	~	~	TE708M
24V Ⓜ	24D	TA714	TC714	TD714	~
24V Diode Ⓜ	24DD	TA714M	TC714M	TD714M	TE714M
36V	36D	TA719	TC719	TD719	~
36V Diode	36DD	~	~	~	TE719M
48V	48D	TA724	TC724	TD724	~
48V Diode	48DD	~	~	~	TE724M
60V	60D	TA774	TC774	TD774	~
60V Diode	60DD	~	~	~	TE774M
64V	64D	TA727	TC727	TD727	~
64V Diode	64DD	~	~	~	TE727
72V	72D	TA728	TC728	TD728	~
72V Diode	72DD	~	~	~	TE728M
80V	80D	TA729	TC729	TD729	~
80V Diode	80DD	~	~	~	TE729M
110V	110D	TA733	TC733	TD733	~
110V Diode	110DD	~	~	~	TE733M
115V	115D	TA734	TC734	TD734	~
115V Diode	115DD	~	~	~	TE734M
125V	125D	TA737	TC737	TD737	~
125V Diode	125DD	~	~	~	TE737M
220V	220D	TA747	TC747	TD747	~
220V Diode	220DD	~	~	~	TE747M
230V	230D	TA749	TC749	TD749	~
230V Suppres.	230DS	~	~	~	TE749F
250V	250D	TA751	TC751	TD751	~
250V Suppres.	250DS	~	~	~	TE751F
Price		55	55	76	96




D.C. coil for CA7-9C...43C contactors (typical) - side view



top view



D.C. coil for CA7-60D...85D contactors (typical) - side view ⑤



top view

- ① Other coil voltages available. Contact your Sprecher + Schuh representative for information.
- ② D.C. Codes in large, bold letters indicate coils that are standard stocked items.
- ③ Voltage operating range: $0.65 \dots 1.3 \times U_s$.
- ④ Voltage operating range: $0.7 \dots 1.25 \times U_s$.
- ⑤ CA7-60D...85D contactors have a two winding coil with built-in late break auxiliary contact and coil suppression.